

Speed Queen

COIN-OPERATED WASHER-EXTRACTORS

20 lb (9 kg) WASHER-EXTRACTOR
25 lb (11 kg) WASHER-EXTRACTOR
30 lb (14 kg) WASHER-EXTRACTOR
40 lb (18 kg) WASHER-EXTRACTOR
60 lb (27 kg) WASHER-EXTRACTOR
80 lb (36 kg) WASHER-EXTRACTOR



Speed Queen®

BUILT BETTER TO LAST LONGER

LET SPEED QUEEN LEAD THE WAY...

Meeting Your Needs

Today's coin laundries need laundry equipment that is flexible, reliable, and delivers excellent cleanability every time. Speed Queen's washer-extractor does just that. We've developed a unit that will fulfill your basic needs and exceed your expectations.

CLEANABILITY Linens last longer when they receive the right care. Our washer-extractors combine cycle flexibility with adjustable cycle times, which can be set as short as 16.5 minutes or as long as 27.5 minutes. Machines come with a factory preset cycle of 21.5 minutes to provide superior washability and fast customer turnover.

flexibility Our activation of the unit is a digital coin drop. Our digital coin drop not only counts down as coins are inserted, but it also acts as a security device. You can determine whether the correct amount of coins has been inserted if equipment fails to operate. The digital drop also allows for vend price alteration. Convenient dip switches allow a maximum of \$15.75 vend charge per cycle.



RELIABILITY At Speed Queen we're confident that our washer-extractors are built better to last longer, so we are offering a three-year limited warranty* to prove it.

Control Options



Electromechanical Timer Control

Speed Queen offers four preset wash formulas to get clothes their cleanest, while maximizing efficiency. Customers can choose from a variety of wash cycles such as hot for heavy soils and whites; warm for medium soils and whites or light soil and permanent press, and cold for all cold water wash, delicates, knits, and lightly soiled fabrics.

As an added convenience, we've incorporated a cycle indicator to keep your customer informed of wash cycle status. This way the customer can determine which wash or rinse step the machine is in. A separate light also informs the customer when to add bleach so there's no question about it.



Fully Programmable B-Micro Control

The B-Micro control is designed to offer you eight pre-programmed cycles. These cycles can be customized to fit your specific needs. By customizing your cycles you can significantly reduce water consumption. Turnaround time also is improved by doing the maximum amount of cleaning in the smallest amount of time. The B-Micro also is very easy to operate with a separate start pad and cycle symbols designed to match garment care labels.



Electronic Coin Drop



Dual Digital Coin Drop



World Coin Drop

Activation Options

Speed Queen offers many activation options to meet your specific market needs.

The coin drop with its all-metal design, reduces coin jamming and provides superior coin validation.

Dual coin drop options are available for various coin denominations.

Using electronic signature recognition technology, the World Coin Drop kit offers superior coin validation and comes pre-programmed to accept coins and/or metallic tokens for your market.

WASHER-EXTRACTORS



Heavy Duty Construction

Durable 304 stainless steel cabinet front, sides and top, as well as inner and outer tubs, won't corrode, chip, crack or pit with normal use, and they're



extremely corrosion resistant. Our heavy-duty Gamma

A-Frame stands up to even the toughest laundry conditions, keeping Speed Queen washer-extractors durable for years to come.

Multi-Compartment Dispenser

Our self-cleaning, multi-compartment dispenser automatically dispenses detergent for prewash and main wash, and fabric softener for final rinse.

Simple user instructions with clearly



marked compartments make it easy for customers to use, promoting proper equipment usage.

Door Lock Delay

In case of power failure, our heavy-duty stainless steel door can be easily opened without the aid of tools or an attendant. After a 60-second time delay has lapsed, customers can remove garments quickly and efficiently.

Large Door Opening

A large door opening makes loading and unloading fast and easy. Our heavy-duty stainless steel door features vacuum tight sealing to keep water inside the machine where it belongs. The door lock, as well as the heat-treated, shatter-proof circular door glass, helps operators safely view the wash process.



Superior Serviceability

Speed Queen's removable top and front panels are designed for minimum down time and ease of service. Now, troubleshooting electrical systems as well as accessing drain valve components is easier than ever.



Reversing Wash Action

The alternate rotating wash action thoroughly cleans your customers' clothes without damaging those delicate fabrics.

Low Water Usage

Speed Queen washer-extractors are designed to save water and energy. This translates into operational efficiency, satisfied customers, and more importantly, bottom line profits.

Heavy-Duty Bearings and Trunion Assembly

Sealed heavy-duty bearings require no lubrication — permanently!
(20 lb - 60 lb models only)

Superior Warranty

At Speed Queen, we're confident that our drying tumblers are built better to last longer and we're offering the following limited warranty to prove it:

Through three years we offer free replacement for any part of the drying tumbler which fails as a result of a defect in material or workmanship after the date of original installation.*

3 YEAR LIMITED WARRANTY

* Parts only, labor not included. See Speed Queen Warranty Bond for specifics.

WASHER-EXTRACTOR SPECIFICATIONS

	SC20	SC25	SC30	SC40	SC60	SC80	
Capacity - lb (kg)	20 (9)	25 (11.3)	30 (13.6)	40 (18)	60 (27)	80 (36)	
Width - in (mm)	26" (660)	26" (660)	29" (737)	30 5/8" (778)	34 1/16" (865)	41 1/2" (1054)	
Depth - in (mm)	29 13/16" (757)	33 13/16" (859)	34 13/16" (884)	40" (1016)	42 15/16" (1091)	52" (1321)	
Height - in (mm)	42 7/8" (1089)	44 7/8" (1140)	45 7/8" (1165)	47 1/2" (1200)	50 13/16" (1291)	56 7/8" (1444)	
Cylinder Diameter - in (mm)	21" (533)	21" (533)	24" (610)	26 1/4" (667)	30" (762)	36" (914)	
Cylinder Depth - in (mm)	13 3/4" (349)	18 3/4" (457)	16" (406)	20 1/4" (514)	22" (559)	22" (559)	
Cylinder Volume - cu. ft. (liters)	2.76 (78.1)	3.76 (106)	4.19 (118)	6.34 (180)	9.0 (255)	12.4 (354)	
Door Opening Size - in (mm)	11 5/8" (295)	11 5/8" (295)	14 11/32" (364)	16 1/4" (413)	16 1/4" (413)	18 1/2" (470)	
Door Bottom to Floor - in (mm)	14 3/8" (365)	14 3/8" (365)	14" (356)	14 1/2" (368)	15" (381)	17 3/4" (451)	
G-Factor (High Extract)	83.1	83.5	73.3	89.9	93.8	40/85/147	
Wash Speed - RPM	57	57	49	51	44	22/41	
Extract Speed - RPM	528	528	464	491	469	280/408/537	
Water Inlet Conn. - in (mm)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	
Drain Diameter - in (mm)	2" (52)	2" (52)	2" (52)	3" (76)	3" (76)	3" (76)	
Drain Height to Floor - in (mm)	4 1/2" (114)	4 1/2" (114)	4" (100)	4 3/4" (121)	5" (127)	5 3/4" (146)	
Motor HP (wash) - HP (kW)	.15 (.11)	.25 (.19)	.24 (.18)	.40 (.30)	.55 (.41)	N/A	
Motor HP (extract) - HP (kW)	.74 (.55)	1.4 (1.04)	1.34 (1.0)	1.8 (1.3)	2.7 (2.01)	5 (3.73)	
Voltage/Hz/Phase* Circuit Breaker-FLA amp	B	120/60/1 • 20-15	N/A	N/A	N/A	N/A	N/A
	C	380-415/50/3 • 15-2	380-415/50/3 • 15-2	380-415/50/3 • 15-2	380-415/50/3 • 15-2	380-415/50/3 • 15-2	N/A
	D	220-240/50/3 • 15-4	220-240/50/3 • 15-2	220-240/50/3 • 15-3	220-240/50/3 • 15-3	220-240/50/3 • 15-4	N/A
	E	220-240/50/1 • 15-4	220-240/50/1 • 15-4	220-240/50/1 • 15-5	N/A	N/A	N/A
	J	200/50/3 • 15-3	200/50/3 • 15-3	200/50/3 • 15-2	200/50/3 • 15-2	200/50/3 • 15-5	N/A
	O	208-240/60/3 • 15-3	208-240/60/3 • 15-2	208-240/60/3 • 15-4	208-240/60/3 • 15-3	208-240/60/3 • 15-4	N/A
	P	N/A	N/A	N/A	N/A	N/A	380-415/50-60/3 • 15-5
	Q	N/A	N/A	N/A	N/A	N/A	220-240/50-60/3 • 15-7
	X	N/A	N/A	N/A	N/A	200-240/50-60/1-3 • 15-4	N/A
	Y	208-240/60/1 • 15-6	208-240/60/1 • 15-5	208-240/60/1 • 15-10	208-240/60/1 • 30-14	N/A	N/A
Shipping Dimensions - in (mm)	H	51" (1295)	53 1/2" (1359)	53 1/2" (1359)	56 1/2" (1422)	58 1/2" (1486)	62 1/2" (1588)
	W	29" (737)	29" (737)	30 1/2" (774)	32" (813)	36" (914)	48" (1219)
	D	32 1/2" (826)	36 1/4" (921)	37 1/2" (953)	41" (1041)	44 1/2" (1130)	56" (1422)
Net Weight - lb (kg)	353 (160)	427 (193)	496 (225)	686 (311)	811 (368)	1346 (610)	
Standard Shipping Weight - lb (kg)	373 (169)	448 (203)	519 (235)	710 (322)	838 (380)	1420 (644)	
Wood Crate Shipping Weight - lb (kg)	461 (209)	536 (243)	600 (272)	810 (367)	947 (430)	1545 (701)	
Agency Approvals	ETL, CE, ETLc	ETL, CE, ETLc	ETL, CE, ETLc	ETL, CE, ETLc	ETL, CE, ETLc	ETL, CE, ETLc	

* Standard domestic voltage 208-240/60/3. Circuit breaker and amp draw data shown is for standard voltage models without auxiliary heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines. CE approval is available on 50 hz 20-60 models.

Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant. Features and certifications may vary by model.

©Copyright 2006 Alliance Laundry Systems LLC



www.speedqueen.com


Speed Queen[®]
Alliance Laundry Systems