

**UniMac**®

**Flatwork Finisher**

**300 mm (12")  
Electric**



***Expert Solutions from the Laundry Experts***

# UniMac 300 mm Flatwork Finisher Specifications

**Electric Heat** - Patented flexible chest, mechanically presses over 210 degrees against a 300 mm (12") padded roll, which ensures: high production, superior finish and short heat-up times (within three minutes).

**Vapor Vacuum** - Occurs through the roll for moisture removal.

**Temperature Control** - Digital display readout showing temperature control level at the chest.

**Variable Speed Frequency** - Inverter control to better match linen requirements.

**Return** - The 300 mm model is equipped with front return.

	UD12F055	UD12F071
Roll Diameter - mm (in)	300 (12")	300 (12")
Finishing Width - mm (in)	1400 (55")	1800 (71")
Ironing Speed - m/m (ft/m)	.8-3 (2.6-9.8)	.8-3 (2.6-9.8)
Capacity Resistances kW (HP)	75 (10)	10 (13)
Roll Motor - kW (HP)	.12 (.16)	.12 (.16)
Exhaust Motor - kW (HP)	.03 (.04)	.03 (.04)
Exhaust Duct - mm (in)	56 (2 1/4")	56 (2 1/4")
Electrical Requirements • Circuit Breaker	208-240/60/3 • 50 230/50/3 • 50 400/50/3 • 25 440-480/60/3 • 25	208-240/60/3 • 60 230/50/3 • 50 400/50/3 • 40 440-480/60/3 • 30
Overall Dimensions L x D x H - mm (in)	1848 x 66 x 1117 (73" x 26" x 44")	2248 x 661 x 1117 (89" x 26" x 44")
Net Weight - kg (lb)	220 (485)	250 (551)
Shipping Weight - kg (lb)	320 (705)	350 (771)
Agency Approval	CE	CE

Ironer models are made to suit a variety of electrical service characteristics. See your UniMac distributor for specifications. For further details on installation, refer to the Installation, Operation and Maintenance Instructions supplied with the ironer.

Due to continuous product improvements, design and specifications are subject to change without notice.

Side Views



Control close-up



AI06-205

[www.uniwash.com](http://www.uniwash.com)

Alliance Laundry Systems  
Shepard Street, Ripon, WI 54971  
Telephone: 920-748-3121

©Copyright 2006 Alliance Laundry Systems LLC

